



VIA Embedded Platform
www.viaembedded.com

Operating Guide

EPIA NL-Series Nano-ITX Mainboard

Table of Contents

TABLE OF CONTENTS	I
VIA EPIA NL-SERIES OVERVIEW	1
VIA EPIA NL-SERIES LAYOUT.....	2
VIA EPIA NL-SERIES SPECIFICATIONS.....	3
VIA EPIA NL PROCESSOR SKUS	4
VIA LUKE COREFUSION™ OVERVIEW	5
VIA EPIA NL-SERIES LAYOUT DIAGRAM & HEIGHT DISTRIBUTION (TOP).....	6
VIA EPIA NL-SERIES LAYOUT DIAGRAM & HEIGHT DISTRIBUTION (BOTTOM).....	7
VIA EPIA NL-SERIES HEAT SINK LAYOUT & HEIGHT DISTRIBUTION	8
VIA EPIA NL-SERIES BOARD COOLING METHOD & HEIGHT DISTRIBUTION.....	9
NOISE LEVEL DATA.....	10
POWER CONSUMPTION.....	11
VIA EPIA NL 5000E	11
VIA EPIA NL 8000E	12
VIA EPIA NL 10000.....	14
POWER SPECIFICATIONS	16
VIA EPIA NL-SERIES MICROSOFT AND LINUX DRIVER SUPPORT	17
MICROSOFT DRIVER SUPPORT.....	17
LINUX DRIVER SUPPORT.....	17
CONTACT	18

VIA EPIA NL-Series Overview


The VIA EPIA NL-Series Nano-ITX Mainboard is an ultra compact x86 motherboard using pin headers design for low profile with unprecedented expandability and versatility for today's ever-growing need of embedded applications. The mainboard is based on the VIA Luke CoreFusion™ processor featuring an embedded hardware MPEG-2 decoder / MPEG-4 accelerator and integrated VIA UniChrome™ Pro 2D/3D graphics for rich digital media performance. With the sizable memory bandwidth of DDR400 SDRAM SODIMM, the high data transfer speeds of ATA-133 and Serial ATA and further enhanced by support of 6-Channel AC'97 codec for Smart 5.1 surround sound, the VIA EPIA NL-Series delivers the increased performance levels required of today's embedded digital media applications.

The latest in high-bandwidth connectivity is supported with up to eight USB 2.0 pin header, as well as an COM / LPC / SIR pin header and one 10/100 Fast Ethernet pin header for extended broadband connectivity. The VIA EPIA NL-Series also offers support for a number of LVDS embedded LCD panels, TV-out, S-Video, Video interface port, CRT VGA / SMBus / CAP0 and has one Mini-PCI slot for expandability options. The VIA EPIA NL-Series is compatible with a full range of Nano-ITX chassis as well as FlexATX and MicroATX enclosures and power supplies.

The VIA EPIA NL-Series is fully compatible with Microsoft® and Linux operating systems and is available in a variety of configurations, including the fanless VIA Luke CoreFusion™ processor for silent system designs.

VIA EPIA NL-Series Layout

VIA EPIA NL Nano-ITX Mainboard
(Dimension 12cm X 12cm)



VIA EPIA NL-Series Specifications

Core Logic	<ul style="list-style-type: none"> - VIA Luke CoreFusion™ processor - VIA VT8237R-series South Bridge
System Memory	<ul style="list-style-type: none"> - 1 DDR400/333/266 SODIMM socket - Up to 1GB memory size
VGA	<ul style="list-style-type: none"> - Integrated VIA UniChrome™ Pro AGP Graphics with MPEG-2 Decoding / MPEG-4 Acceleration
Expansion Slot	<ul style="list-style-type: none"> - 1 Mini-PCI
Onboard IDE	<ul style="list-style-type: none"> - 2 UltraDMA 133/100/66 connectors (Secondary 2.0mm 44-pin header)
Onboard S-ATA	<ul style="list-style-type: none"> - 1 Serial ATA connector
Onboard LAN	<ul style="list-style-type: none"> - VIA VT6103L 10/100 Base-T Ethernet PHY
Onboard Audio	<ul style="list-style-type: none"> - VIA VT1617A 6 channel AC'97 Codec
Onboard TV Out	<ul style="list-style-type: none"> - VIA VT1625 HDTV Encoder
Onboard I/O Connectors	<ul style="list-style-type: none"> - 1 USB pin header for 8 additional USB 2.0 ports - 1 SIO pin header (including COM port, SIR and LPC support) - 1 KBMS pin header (Switchable for KB/MS connector) - 2 FAN connectors (CPU FAN and SYS FAN) - 1 LVDS / DVI connector (an add-on card is required) - 1 Audio pin header for Line-out, Line-in, Mic-in, CD-in and S/PDIF out - 1 TV Out pin header for S-Video, Composite, and Component (YPbPr/Scart/D-Terminal) - 1 LAN pin header for 10/100 Ethernet LAN port - 1 CRT pin header (including VGA port, SMBUS and CAPO) - 1 Front-Panel pin header - 1 +12V Nano-ITX power connector
BIOS	<ul style="list-style-type: none"> - Award BIOS - 4/8Mbit flash memory
System Monitoring & Management	<ul style="list-style-type: none"> - CPU temperature monitoring - CPU voltage monitoring - Wake-on-LAN, Keyboard-Power-on, Timer-Power-on Watch Dog Timer, FAN control - System power management - AC power failure recovery
Operating Temperature	<ul style="list-style-type: none"> - 0°C up to 47°C ~ 50°C (by different product items)
Operating Humidity	<ul style="list-style-type: none"> - 0% ~ 95% (relative humidity; non-condensing)
Form Factor	<ul style="list-style-type: none"> - Nano-ITX (8 Layer) - 12 cm x 12 cm

* The specification is subject to change without prior notice.

VIA EPIA NL Processor SKUs

The VIA EPIA NL-Series is available in 533MHz, 800MHz and 1.0GHz speed grades. The VIA EPIA NL utilizes VIA's ultra low power VIA Luke Core Fusion™ processor.



PadLock ACE US government approved Advanced Encryption Standard (AES), performing cryptographic functions for securing e-mails, personal files, online transactions, and networks.



PowerSaver 3.0 technology, extends battery life by dynamically altering the voltage and clock frequency to reduce power consumption when the processor is not required to run at full speed.




The VIA FLiteDeck™ Suite, an advanced system management suite that enables to user to effortlessly track and monitors mission critical system data and enable seamless live Windows®-based BIOS updates as well as comprehensive BIOS status information.


VIA Luke CoreFusion™ Overview

The Luke CoreFusion™ Processor is a high performance, cost-effective and energy efficient processor with integrated UniChrome Pro graphics / video controller. The [Luke CoreFusion™ Processor](#) integrates VIA's most advanced system controller with high-performance UniChrome Pro 3D / 2D graphics and video controller, DVI monitor and TV-Out interfaces. And provides superior performance between the DRAM, V-Link and internal or external AGP 8x graphics controller with pipelined, burst and concurrent operation. The VT8237R-series South Bridge is a highly integrated peripheral controller which includes Serial ATA, Ultra DMA IDE, USB 2.0, 10/100 MB networking MAC, AC'97 and system power management.


The complete system consists of the Luke CoreFusion™ Processor and the VT8237R-series V-Link South Bridge on the EPIA NL board.




VIA EPIA NL-Series Layout Diagram & Height Distribution (Top)




VIA EPIA NL-Series Layout Diagram & Height Distribution (Bottom)



VIA EPIA NL-Series Heat Sink Layout & Height Distribution



VIA EPIA NL-Series Board Cooling Method & Height Distribution



Noise Level Data

VIA and the EPIA series have been at the forefront of the quiet computing initiative. The VIA EPIA NL-Series has been designed to be totally non-obtrusive with noise levels equivalent to a person whispering. With noise levels ranging from the totally silent VIA EPIA NL10000, VIA EPIA NL8000E, and VIA EPIA NL5000E, a new wave of system design innovation and exciting opportunities are being created in an almost limitless number of emerging new market segments - ranging from fanless thin clients, flat panel small form factor desktop replacement systems, LCD PCs and a host of other space and power saving systems.

Common Sounds	dBA Level
Threshold of hearing	0 dBA
VIA EPIA NL5000E	0 dBA
VIA EPIA NL8000E	0 dBA
VIA EPIA NL10000	20 dBA
Normal breathing	10 dBA
Whispering at 1 meter	20 dBA
Conventional PC	35 – 50 dBA
Rainfall	50 dBA
Normal speech	60 dBA

The dBA scale is logarithmic, i.e. 10 dBA represents a doubling in volume. dBA values are measured at a distance of one meter.

Power Consumption

Power consumption tests were carried out comparing the VIA EPIA NL5000E (running the 533MHz VIA CoreFusion™ processor), VIA EPIA NL8000E (running the 800MHz VIA CoreFusion™ processor) and VIA EPIA NL10000 (running the 1.0GHz VIA CoreFusion™ processor). The following tables are a comprehensive breakdown of the EPIA platform's voltage, amp and wattage values while running common system applications.

VIA EPIA NL 5000E

A. Playing DVD – Power DVD 5.0

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.235	2.971	9.611
Main Board +5V	5.045	0.914	4.611
Main Board 5VSB	4.915	0.053	0.260
Main Board +12V	11.996	0.102	1.224
Main Board Power Consumption			15.706

B. Playing MP3 – Media Player

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.236	2.815	9.109
Main Board +5V	5.043	0.794	4.004
Main Board 5VSB	4.912	0.053	0.260
Main Board +12V	11.992	0.104	1.247
Main Board Power Consumption			14.621

C. Running Network Application – File Copy

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.252	2.650	8.618
Main Board +5V	5.063	0.511	2.587
Main Board 5VSB	4.927	0.060	0.296
Main Board +12V	11.995	0.106	1.271
Main Board Power Consumption			12.772

D. Idle

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.252	2.571	8.361
Main Board +5V	5.059	0.441	2.231
Main Board 5VSB	4.921	0.053	0.261
Main Board +12V	11.983	0.101	1.210
Main Board Power Consumption			12.063

E. Run C.C. Winstone 2001

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.244	2.754	8.934
Main Board +5V	5.052	0.886	4.476
Main Board 5VSB	4.922	0.057	0.281
Main Board +12V	12.005	0.103	0.000
Main Board Power Consumption			13.691

F. S3 Mode

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	0.000	0.000	0.000
Main Board +5V	0.000	0.000	0.000
Main Board 5VSB	4.963	0.160	0.794
Main Board +12V	0.000	0.000	0.000
Main Board Power Consumption			0.794

VIA EPIA NL 8000E
A. Playing DVD – Power DVD 5.0

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.230	2.968	9.587
Main Board +5V	5.041	1.081	5.449
Main Board 5VSB	4.912	0.055	0.270
Main Board +12V	11.996	0.104	1.248
Main Board Power Consumption			16.554

B. Playing MP3 – Media Player

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.239	2.839	9.196
Main Board +5V	5.046	1.053	5.313
Main Board 5VSB	4.918	0.055	0.270
Main Board +12V	12.005	0.105	1.261
Main Board Power Consumption			16.040

C. Running Network Application – File Copy

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.252	2.644	8.598
Main Board +5V	5.064	0.585	2.962
Main Board 5VSB	4.927	0.056	0.276
Main Board +12V	11.995	0.104	1.247
Main Board Power Consumption			13.084

D. Idle

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.258	2.566	8.360
Main Board +5V	5.064	0.496	2.512
Main Board 5VSB	4.928	0.057	0.281
Main Board +12V	11.993	0.110	1.319
Main Board Power Consumption			12.472

E. Run C.C. Winstone 2001

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.238	2.735	8.856
Main Board +5V	5.044	1.143	5.765
Main Board 5VSB	4.917	0.055	0.270
Main Board +12V	12.008	0.101	0.000
Main Board Power Consumption			14.892

F. S3 Mode

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	0.000	0.000	0.000
Main Board +5V	0.000	0.000	0.000
Main Board 5VSB	4.962	0.160	0.794
Main Board +12V	0.000	0.000	0.000
Main Board Power Consumption			0.794

VIA EPIA NL 10000
A. Playing DVD – Power DVD 5.0

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.236	2.965	9.595
Main Board +5V	5.036	1.277	6.431
Main Board 5VSB	4.911	0.064	0.314
Main Board +12V	11.987	0.158	1.894
Main Board Power Consumption			18.234

B. Playing MP3 – Media Player

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.245	2.900	9.411
Main Board +5V	5.039	1.349	6.798
Main Board 5VSB	4.915	0.061	0.300
Main Board +12V	12.002	0.157	1.884
Main Board Power Consumption			18.392

C. Running Network Application – File Copy

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.254	2.641	8.594
Main Board +5V	5.060	0.673	3.405
Main Board 5VSB	4.925	0.064	0.315
Main Board +12V	11.988	0.160	1.918
Main Board Power Consumption			14.232

D. Idle

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.265	2.592	8.463
Main Board +5V	5.062	0.555	2.809
Main Board 5VSB	4.926	0.061	0.300
Main Board +12V	11.990	0.160	1.918
Main Board Power Consumption			13.491

E. Run C.C. Winstone 2001


	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	3.235	2.777	8.984
Main Board +5V	5.035	1.445	7.276
Main Board 5VSB	4.914	0.062	0.305
Main Board +12V	11.999	0.157	0.000
Main Board Power Consumption			16.564

F. S3 Mode

	Measured Voltage	Measured Amp.	Watts
Main Board +3.3V	0.000	0.000	0.000
Main Board +5V	0.000	0.000	0.000
Main Board 5VSB	4.962	0.163	0.809
Main Board +12V	0.000	0.000	0.000
Main Board Power Consumption			0.809

Power Specifications

The EPIA NL utilizes an industry standard 12-pin ATX main connector to the power supply. Due to the EPIA NL platform's ultra low power requirements, a 90 – 120 Watt ATX power supply is ample for even the heaviest of multimedia system applications.

Nano-ITX PWR					
1		2			
		3		7	-PSON
		4		8	+5V
		5		9	GND
		6		10	+5V
				11	GND
				12	PWRGD

VIA EPIA NL-Series Microsoft and Linux Driver Support

Microsoft Driver Support

VIA EPIA NL-Series offer full support for the complete range of Microsoft operating systems.

For standard operating systems, Windows 98/Me/2000/XP latest drivers downloads can be found in the VEPD website at www.viaembedded.com.

For embedded operating systems, Windows CE.NET and XP Embedded related driver supports can be found in the VIA Arena website at www.viaarena.com.

Linux Driver Support

VIA EPIA NL mainboards have a very high degree of support under Linux.

Support and drivers are provided through various methods including:

- Drivers provided by VIA
 - Using a driver built into a distribution package
 - Visiting VIA Arena website at www.viaarena.com for latest updates on a monthly basis
- Installing a third party driver (such as the ALSA driver from the Advanced Linux Sound Architecture project for integrated audio)

For OEM clients and system integrators developing a product for long-term production, other code and resources may also be made available. You can submit a request either through the [Developers portal](#) on VIA Arena, or through your VEPD support contact. Alternatively, VIA can work further towards providing additional drivers to suite your specific needs.

Contact

For more information on the VIA EPIA NL-Series Nano-ITX Mainboard contact your sales representative or visit our website at www.viaembedded.com

USA

440 Mission Court, Suite 220
Fremont, CA 94539
Tel: (510) 683 3300
Fax: (510) 687 4654
Email: vpsd_sales@viatech.com

Germany

Mottmann Strasse 12
53842 Troisdorf-Oberlar
Tel: 2241 397780
Fax: 2241 3977819
Email: sales@via-tech.de

Taiwan

1F, 531, Chung Cheng Road
Hsin Tien, Taipei
Tel: (02) 2218 5452
Fax: (02) 2218 5453
Email: mkt@via.com.tw

China

6F, DAscom Tower
9 Shangdi East Road
Haidian District
Beijing, 100085
Tel: 10 6296 3088
Fax: 10 6297 2929
Email: vpsdbj@viatech.com.cn